

Laten HOT or **COLD** in the one shelf

People who serve, products that solve."

Great flexibility to suit your venue with surfaces to match any decor, available in drop-in or bottom mount with traditional or Swanstone® stone finish

From the world-wide leaders in food holding solutions comes this versatile shelf to satisfy your differing serving needs at the touch of a button. Serve hot buffet or cool salads/sweets on the same shelf space easily and quickly.

Easily change between Hot or Cold in approximately 30 minutes to suit your needs

- Control Box can be remotely mounted up to 1,229m from centre of the shelf
- Durable Hardcoat Traditional Aluminium Finish Drop-In or Flush Mount model or ...
- Swanstone[®] food safe stone colours available to match your decor and other Hatco heated shelves
- Famous Hatco performance and reliability
- Patent-pending thermal break reduces condensation and temperature transfer.

Includes a remote-mountable control enclosure. with a three position power switch and two digital temperature controllers.





Hot/Cold Built-In Shelves

Models: HCSBF-24-I, -36-I, -48-I

HCSBF MODELS (Hot Cold Shelf, Aluminium Hard Coat - Built-in Flush)



SPECIFICATIONS

CODE	DESCRIPTION	DIMENSIONS: (heated-cooled/overall)	Watts / Amps	Compressor	Weight
HCSBF-24-I	Drop-In Hot / Cold Shelf - Hardcoat	610W x 495mmD / 648W x 533mmD	804 / 3.5	1/4HP	58Kg
HCSBF-36-I	Drop-In Hot / Cold Shelf - Hardcoat	914W x 495mmD / 953W x 533mmD	1044 / 4.5	1/3HP	68Kg
HCSBF-48-I	Drop-In Hot /Cold Shelf - Hardcoat	1219W x 495mmD / 1257W x 533mmD	1044 /4.5	1/3HP	84Kg
HCSSBF-24-I	Drop-In Hot /Cold Shelf - Swanstone*	610W x 495mmD	804 / 3.5	1/4HP	67Kg
HCSSBF-36-I	Drop-In Hot /Cold Shelf - Swanstone*	914W x 495mmD	1044 / 4.5	1/3HP	76Kg
HCSSBF-48-I	Drop-In Hot /Cold Shelf - Swanstone*	1219W x 495mmD	1044 / 4.5	1/3HP	92Kg

*Swanstone Colour must be specified at time of order. Colours available: Granite Gray, Bermuda Sand and Night Sky. (See colour samples previous page)

COUNTERTOP CUTOUT SIZE

MODEL	WIDTH		DEPTH	
	Minimum	Maximum	Minimum	Maximum
HCSBF-24-I	625 mm	635 mm	511mm	521 mm
HCSBF-36-I	930 mm	940 mm	511 mm	521 mm
HCSBF-48-I	1234 mm	1245 mm	511 mm	521 mm
	WIDTH	DEPTH		
	with 10 mm radii	with 10 mm radii		
HCSSBF-24-I	619 mm	505 mm		
HCSSBF-36-I	924 mm	505 mm		
HCSSBF-48-I	1229 mm	505 mm		
	WIDTH	DEPTH		
CONTROL BOX	(should not exceed)	(should not exceed)		
	332 mm	146 mm		



Remote control with three position switch and two electronic temperature controls

